



Valentino
VENETIAN PLASTER FINISHES

Coverage

Approximately 280-400 ft² per gallon.

Coverage may vary due to ambient temperature, surface temperature, surface porosity, mixing method, and/or application method.

Packaging

1 Gal. (3.8L), 11lb (5kg) pails
5 Gal. (18.9L), 55lb (25kg) pails

Storage

1. Store containers in a cool, dry location.
2. Store at a temperature between 45°F (7°C) and 90°F (32°C).
3. Do not store in direct contact with the ground and/or concrete.
4. Store out of direct sunlight.
5. Protect containers from weather and other damage.

Color

Packaged white

Properties

VOC Level: 25 g/L
Permeability: 14 perms

Valentino Mineral Primer

A Silicate Priming Agent



Valentino Mineral Primer is a resin and silicate priming agent specially formulated to promote superior adhesion, workability, and long-term performance of the Valentino lime-based finishes. All substrates should be primed using Valentino Mineral Primer prior to the application of Valentino lime-based plasters.

FEATURES	BENEFITS
Silicate enhanced	Creates a chemical bond with the lime-based finishes to improve adhesion strength
Water-resistant	Helps to seal substrate to prevent efflorescence and stains
Uniform Suction	Improves finish workability and coverage
Water-based	Easy clean up
Vapor Permeable	Allows wall to naturally breath which aids drying and helps to prevent mold or blistering
VOC Compliant	Low odor and toxicity
High pH Resistant	Can withstand the high pH of lime-based finishes

Basic Uses

Valentino Mineral Primer may be applied over the following substrates: One-coat stucco, brown coat, masonry, poured-in-place and/or tilt-up concrete, approved Omega lime-based finishes, interior finished drywall, veneer plaster and approved Omega base coats.

Omega Products International
1681 California Ave. Corona, CA 92881
P 951.737.7447 • F 951.520.2594
valentinoproducts.com

V104
JUNE 2015



Valentino Mineral Primer

A Silicate Priming Agent

Surface Preparation

Refer to the Valentino finish data sheet Surface Preparation section for additional requirements. All surfaces to receive application must be clean and free of debris, dirt and dust, efflorescence, grease, oils, curing agents, and cleaning solutions. Ensure that all surfaces are smooth and free of any irregularities. Repair all cracks with the appropriate patching material for the existing substrate. Painted or glossy surfaces must be roughened to ensure a proper bond. One coat and three coat stucco products must be cured for a minimum of 7 days and concrete must cure for a minimum of 28 days.

Mixing

Valentino Mineral Primer should be thoroughly mixed prior to use with a paddle-type mixer.

Application

Valentino Mineral Primer may be applied with a brush, roller, or sprayer. Avoid puddling.

1. Ensure that the receiving surface has been properly prepared according to the Surface Preparation section of this Product Data Sheet.
2. Apply Valentino Mineral Primer to the surface. If spraying, be sure to strain and use in an appropriate spraying apparatus.

Drying

Drying time may vary due to climatic conditions, but should not take more than 24 hours at an ambient and surface temperature of 70°F (21°C) and 55% R.H. Variations in ambient and surface temperature and humidity may prolong drying time. All freshly applied material must be protected by an approved protective system from inclement weather until fully dry. It is the responsibility of the applicator to determine if the product is fully cured and/or dry prior to exposing it to rain, snow, dew, and/or any other inclement weather condition that may be detrimental to the product.

Limitations

DO NOT apply product when the ambient and surface temperature is below 40°F (4°C). The ambient and surface temperature must maintain the above requirements until fully dry (See DRYING). Material that is allowed to freeze may suffer irreparable damage. Protect all work from inclement weather with an approved protective system until fully dry.

DO NOT add any other materials to the mixture of the product without written approval from Omega Products International, Inc.

DO NOT deviate in the mixing or application procedures contained in this, or any other Product Data Sheets, without written approval from Omega Products International, Inc.

DO NOT apply Valentino Mineral Primer if there are contaminants on the receiving surface. Contaminates may include, but are not limited to, dust, debris, efflorescence, and/or oils.

DO NOT apply Valentino Mineral Primer to a wet surface.

DO NOT use a paddle-type mixer that exceeds 500 RPM.

DO NOT leave Valentino Mineral Primer in its applied state (finish coat required).

NOTE: Failure to follow manufacturer's written specifications could result in the following, but not limited to spalling, cracking, peeling, chipping, delamination, discoloration, wash off, and overall system failure.

Cleaning

Cleaning may be accomplished with water immediately after use.

Safety

Avoid contact with eyes or prolonged contact with skin. Wash thoroughly after handling. In case of eye contact, flush immediately with running water for at least 15 minutes. Consult a physician immediately. Do not take internally. Be sure to provide adequate ventilation in enclosed areas. Use of an approved respirator is recommended.

KEEP OUT OF REACH OF CHILDREN

Disclaimer

Omega Products International, Inc. [Manufacturer] MAKES NO WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE WITH RESPECT TO THE PRODUCT(S) SOLD HEREIN. The recommendations, suggestions, statements and technical data are based on the best knowledge available to Manufacturer and are given for informational purposes ONLY and without any responsibility for their use. It is expressly understood and agreed, as a condition of the use of this product, that the buyer's sole and exclusive remedy for any claimed defective product against Manufacturer shall be the replacement of products actually proven to be defective. Handling and use of the products are beyond the control of Manufacturer; therefore,

no warranty is made, expressed or implied, as to the results obtained from the use of the product or against any claims for infringement of patents resulting from use of the product. Under no circumstance shall Manufacturer be liable for incidental or consequential damages arising out of the use or the improper application of the product. Before applying the product, the user shall determine the suitability of the product for his/her independent use, assuming all risks and liability whatsoever in connection therewith. This writing constitutes a complete and exclusive statement of the understanding between Manufacturer and Buyer.

Claims

Any Claimant shall notify Manufacturer immediately in writing of any alleged defect in the material. Claimant will provide Manufacturer with a reasonable and exclusive opportunity to investigate and test for the alleged defect. For any claim that is not valid Claimant agrees to pay Omega's reasonable charges, including travel and labor associated with investigation of such claim. Technical Assistance Technical assistance and information is available by calling Omega Products International, Inc. at (800) 600-6634 or FAX (951) 520-2594 or by e-mail at info@omega-products.com.

Warranty

The following is made in lieu of all expressed and implied rights, warranties and conditions, statutory or otherwise. The manufacturer's only obligation shall be to replace such quantity of products proven to be defective within one year following the date of manufacture, provided that the alleged defective product is returned prepaid to the manufacturer's plant and is accompanied with proof of purchase and batch number.

