



*Valentino*  
VENETIAN PLASTER FINISHES

# Valentino Top Coat

Wax & Metallic Topcoats

## Coverage

Approximately 100-600 ft<sup>2</sup> in a one coat application.

Coverage may vary due to ambient temperature, surface temperature, surface porosity, mixing method, and/or application method.

## Packaging

16 oz (68 g) wide mouth jars

## Storage

1. Store containers in a cool, dry location.
2. Store at a temperature between 45°F (7°C) and 85°F (30°C).
3. Do not store in direct contact with the ground and/or concrete.
4. Store out of direct sunlight.

## Color

Available in clear, brown, silver, copper, interference gold, and interference green.



BEL MARMO  
BL-002  
BROWN WAX



VENEZIA  
VZ-013  
GOLD WAX



TADELAKT  
TK-005  
CLEAR WAX



TADELAKT  
TK-009  
INTERFERENCE GREEN WAX



TADELAKT  
TK-011  
COPPER WAX



VENEZIA  
VZ-007  
SILVER WAX

A mixture of wax, resins, oils, pigments and fine metallic particles designed to increase the polish level on and give accent tones to plaster surfaces.

FEATURES	BENEFITS
Multiple colors	Capable of create a variety of appearances
High sheen	Can create high gloss surface
Water-resistant	Helps to seal substrate to prevent stains
Easy clean up	Cleans with water
Vapor Permeable	Allows wall to naturally breath which aids drying and helps to prevent mold or blistering
VOC Compliant	Low odor and toxicity

## Basic Uses

For interior use over Bel Marmo, Venezia, and Tadelakt.



# Valentino Top Coat

Wax & Metallic Topcoats

## Mixing

Material is already premixed and ready to use.

## Application

1. Valentino Topcoats may be applied with a clean white cotton cloth or a clean stainless steel trowel.
2. To increase the topcoat's sheen, the topcoats may be buffed using a clean cotton cloth or buffer with suitable cotton pad after the wax has dried.

## Drying

Allow to dry for a minimum of 1 hour.

## Limitations

DO NOT apply product when the ambient and surface temperature is below 45°F (7°C) or above 85°F (30°C). Material that is allowed to freeze may suffer irreparable damage.

DO NOT use in constantly wet areas.

DO NOT add any other materials to the mixture of the product without written approval from Omega Products International, Inc. DO NOT deviate in the mixing or application procedures contained in this, or any other Valentino Product Data Sheet, without written approval from Omega Products International, Inc.

DO NOT apply if there are contaminants on the receiving surface. Contaminates may include, but are not limited to, dust, debris, efflorescence, and/or oils.

NOTE: Failure to follow manufacturer's written specifications could result in the following, but not limited to spalling, cracking, peeling, chipping, delamination, discoloration, wash off, and overall system failure. Due to job conditions beyond the control of Omega Products International, Inc., we make no warranty as to the acceptance of the final color. The actual integrally colored finish should be applied on a sample section of the project and verified for color accuracy prior to the actual application process.

## Cleaning

Cleaning may be accomplished with water immediately after use. Use mineral spirits if water does not clean sufficiently.

## Safety

Avoid contact with eyes or prolonged contact with skin. Wash thoroughly after handling. In case of eye contact, flush immediately with running water for at least 15 minutes. Consult a physician immediately. Do not take internally. Be sure to provide adequate ventilation in enclosed areas. Use of an approved respirator is recommended.

KEEP OUT OF REACH OF CHILDREN

**Disclaimer**  
Omega Products International, Inc. [Manufacturer] MAKES NO WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE WITH RESPECT TO THE PRODUCT(S) SOLD HEREIN. The recommendations, suggestions, statements and technical data are based on the best knowledge available to Manufacturer and are given for informational purposes ONLY and without any responsibility for their use. It is expressly understood and agreed, as a condition of the use of this product, that the buyer's sole and exclusive remedy for any claimed defective product against Manufacturer shall be the replacement of products actually proven to be defective. Handling and use of the products are beyond the control of Manufacturer; therefore,

no warranty is made, expressed or implied, as to the results obtained from the use of the product or against any claims for infringement of patents resulting from use of the product. Under no circumstance shall Manufacturer be liable for incidental or consequential damages arising out of the use or the improper application of the product. Before applying the product, the user shall determine the suitability of the product for his/her independent use, assuming all risks and liability whatsoever in connection therewith. This writing constitutes a complete and exclusive statement of the understanding between Manufacturer and Buyer.

**Claims**  
Any Claimant shall notify Manufacturer immediately in writing of any alleged defect in the material. Claimant will provide Manufacturer with a reasonable and exclusive opportunity to investigate and test for the alleged defect. For any claim that is not valid Claimant agrees to pay Omega's reasonable charges, including travel and labor associated with investigation of such claim.  
**Technical Assistance**  
Technical assistance and information is available by calling Omega Products International, Inc. at (800) 600-6634 or FAX (951) 520-2594 or by e-mail at info@omega-products.com.

**Warranty**  
The following is made in lieu of all expressed and implied rights, warranties and conditions, statutory or otherwise. The manufacturer's only obligation shall be to replace such quantity of products proven to be defective within one year following the date of manufacture, provided that the alleged defective product is returned prepaid to the manufacturer's plant and is accompanied with proof of purchase and batch number.

